



# THE EUCLID CHEMICAL COMPANY

19218 REDWOOD ROAD • Cleveland, OH 44110  
(216) 531-9222 • (800) 321-7628 • FAX (216) 531-9596  
www.euclidchemical.com

## EUCO SUPER SLIP

### ◆ ◆ ◆ ◆ ◆ CONCRETE FORM RELEASE AGENT

- ◆ XENG.SPECS      ◆ CATALOG INDEX
- ◆ MSDS            ◆ SECTION INDEX
- ◆ FRENCH         ◆ PRINT
- ◆ SPANISH        ◆ EXIT CATALOG

**EUCO SUPER SLIP** is a concrete form release agent that provides quick, easy and clean release of concrete from forms. It produces a smooth, flat surface, free of voids and defects. It will not transfer from forms, and it leaves concrete surface unstained, ready for paint, plaster or similar treatments. Forms are ready for re-use almost instantly.

#### PRIMARY APPLICATIONS

- Form release for metal, wood, plastic and fiberglass forms
- Concrete molds, overlaid plywood and fiberglass
- Equipment maintenance-scoots, bucket hoists and paving machines
- Aluminum and steel windows

#### FEATURES / BENEFITS

- Reactive type - Does not contain diesel oil
- Non-staining - will not wash off
- Cuts clean-up time
- Eliminates voids, defects, build-up of concrete and mortar
- Protects forms from rusting
- Economical and easy to use

#### SPECIFICATIONS / COMPLIANCES

- NavDock Specifications No. 56359/64
- Corps of Engineers Specifications CE-204
- Many County and Municipal Specifications
- This product meets V.O.C. contents in accordance to EPA 40 CFR Part 59 Table I Subpart D for Form Release Compounds with a maximum V.O.C. content of 450 g/l.

#### PACKAGING

EUCO SUPER SLIP is packaged in 55 gal (208 liter) drums and 5 gal (18.9 liter) pails.

**Shelf life** is 2 years in original, unopened package.

#### TECHNICAL INFORMATION

EUCO SUPER SLIP is a blend of natural and synthetic chemicals that employ a chemical reaction to provide the concrete release. EUCO SUPER SLIP contains a rust inhibitor to protect metal forms and a preservative to increase the life of wood forms. EUCO SUPER SLIP is a reactive type release agent and does not contain diesel oil.

#### Appearance

EUCO SUPER SLIP is a free flowing light brown liquid. EUCO SUPER SLIP will not stain gray or white concrete.

**V.O.C.:** ..... 272 g/l

#### COVERAGE

1 gal (3.8 liter) of EUCO SUPER SLIP will cover approximately 800-1500 ft<sup>2</sup> (74-139 m<sup>2</sup>) of forms depending upon application method and material of the form.

#### DIRECTIONS FOR USE

**Surface Preparation**-For best results, forms should be cleaned of all old concrete before application of EUCO SUPER SLIP.

**Mixing**-EUCO SUPER SLIP requires no pre-mixing before applications. The product should be used directly from the container.

**Placement**-EUCO SUPER SLIP is applied by brush, roller or pump-up type sprayer. Coated forms may be used 1/2 hour after application of EUCO SUPER SLIP.

#### CLEAN-UP

Clean tools and equipment with solvent such as EUCO SOLVENT, xylene or toluene.

**PRECAUTIONS / LIMITATIONS**

- Thick applications may require extra drying time.
- Always wear protective clothing (rubber gloves, eye protection, etc...).
- Do not use as a bond breaker for tilt up concrete construction.

Form Euco Super Slip-9.99

**WARRANTY:** The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for six (6) months from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.