



THE EUCLID CHEMICAL COMPANY

19218 REDWOOD ROAD • Cleveland, OH 44110
(216) 531-9222 • (800) 321-7628 • FAX (216) 531-9596
www.euclidchemical.com

EUCO TF 2018



WEAR AND HEAT RESISTANT REPAIR MORTAR

- XENG.SPECS ◆ CATALOG INDEX
- ◆ MSDS ◆ SECTION INDEX
- XFRENCH ◆ PRINT
- ◆ SPANISH ◆ EXIT CATALOG

EUCO TF 2018 is a unique concrete repair system, combining tough, graded aggregate, specialty cements, and chemical agents. EUCO TF 2018 affords high resistance to impact and abrasion conditions. It provides excellent surface durability for high traffic areas of floors and other surfaces which cannot be closed or shutdown easily or economically. The unique nature of this material also offers high temperature stability as well as chemical resistance not normally found in a cementitious system. With its excellent high early strength, floors may be returned to service 24 hours after placement.

PRIMARY APPLICATIONS

- Industrial floors
- Warehouses
- Loading docks
- Sluiceways
- Maintenance garages for heavy duty equipment
- High traffic aisleways
- Resource recovery
- Towveyors
- Metal processing areas

FEATURES / BENEFITS

- Provides a high early strength, impact resistant wearing surface.
- Gives abrasion resistance far superior to that of plain, cured concrete.
- Aggregate is non-rusting and highly abrasion resistant.
- Provides a dense surface to resist penetration of oil, grease and many other liquids.
- Virtually non-dusting in service.
- Will withstand temperatures in excess of 2000°F (1093°C). A 2" (50mm) min. thickness is required for applications involving heat resistance.
- Resistant to weak organic acids.
- Pumpable through standard concrete pumping equipment

COVERAGE RATES

12.5 lb/ft² (61 kg/m²) at 1" (25 mm)
25 lb/ft² (122 kg/m²) at 2" (50 mm)

TECHNICAL INFORMATION

Typical Engineering Data

The following results were developed under laboratory conditions.

Compressive Strength

2"(50 mm) cubes ASTM C109

<u>Age</u>	<u>Strength</u>
4 hours	4,000 psi (28 MPa)
12 hours	6,000 psi (41 MPa)
1 day	10,000 psi (69 MPa)
3 days	11,000 psi (76 MPa)
7 days	12,000 psi (83 MPa)
28 days	13,000 psi (90 MPa)

Flexural Strength, ASTM C78

<u>Age</u>	<u>Strength</u>
14 days	1,800 psi (12 MPa)
28 days	2,000 psi (14 MPa)

PACKAGING

EUCO TF 2018 is packaged in 70 lb. (32 kg) bags with polyethylene liners for moisture protection. EUCO TF 2018 is also available in bulk 3300 lb (1497 kg) bags for large placements.

YIELD

One 70 lb. (32 kg) bag when mixed with .56 gallons (2.1 liter) of water will yield approximately 0.46 ft³ (0.013 m³) of topping or enough material to cover 5.5 ft² (0.51 m²) at 1" (25 mm) thickness.

DIRECTIONS FOR USE

Surface Preparation-The surface over which EUCO TF 2018 is to be placed must be free of all loose dust, dirt, debris and unsound concrete. The surface texture must have a profile of 1/4" (6.4 mm) or more. The best methods for roughening are scabbling and milling. Questionable concrete that cannot be properly cleaned and textured should be profiled and anchored with mechanical studs to assure an integral bond. EUCO TF 2018 may be placed monolithically on fresh concrete.

Bonding

Monolithic Placement

The surface of the fresh concrete must be 'tined' to provide a profile of 1/4" and a series of 3" long nail-type anchors placed on 16" center around the perimeter of the concrete...each protruding 1/2" into the subsequent topping. The EUCO TF 2018 may be placed anytime within the next 24 hours.

Applications below 150°F (65°C)(existing concrete)

After proper surface preparation, use EUCO #452 MV as a bonding agent. Application rate will be approximately 75 ft²/gal. over a 1/4" profiled surface.

Applications above 150°F (65°C)(existing concrete)

After proper surface preparation, broom apply a bond coat utilizing EUCO TF 2018.

Mixing-Bags of EUCO TF 2018 should be mixed with a rotary type concrete mixer or paddle type mortar mixers in good running condition. Mix 2 to 4 bags per batch using .56 gallons (2.1 liter) of water per bag. Add the water to the mixer first and follow with the EUCO TF 2018 powder. Mix thoroughly for 3 to 5 minutes until achieving a 9" to 10" (225-250 mm) slump. Contact The Euclid Chemical Company for instructions on mixing bulk bags.

Placement-EUCO TF 2018 can be placed by direct discharge, buggy, wheelbarrow or pump. Working time is approximately 30 minutes. EUCO TF 2018 is placed at a 6" to 8" (150-200 mm) slump and should be screeded to the proper level. Use of an evaporation retardant (Eucobar) is recommended after placement.

Finishing-The finish may be acceptable after initial placement providing a slightly textured surface. Light hand troweling may be done, for a smoother finish, as the material sets. The surface must be covered with polyethylene while waiting to finish.

Curing-Proper curing of EUCO TF 2018 is very important.* Proper curing procedures are important to ensure the durability and quality of the topping. To prevent surface cracking, cure the floor as soon as possible with two coats of a high solids curing compound, such as SUPER AQUA-CURE VOX or SUPER REZ-SEAL.

If use of a curing compound is not desired, wet cure for a minimum of three (3) days. After 3 days of curing EUCO TF 2018 should be allowed to dry out for 5 days before exposure to high temperatures. Exposure to high temperatures without a drying period can result in cracking, or pop-out scaling.

* When placing at thicknesses over 1" (25 mm) significant heat may be given off. The topping temperature must be maintained at less than 100°F (38°C) to avoid thermal cracking. Application of cool water during the first 48 hours of curing is recommended.

PRECAUTIONS / LIMITATIONS

- Do not use over air-entrained concrete when placing monolithically.
- Proper curing is required.

Form Euco TF 2018-9.99

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for six (6) months from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.