



THE EUCLID CHEMICAL COMPANY

19218 REDWOOD ROAD • Cleveland, OH 44110
(216) 531-9222 • (800) 321-7628 • FAX (216) 531-9596
www.euclidchemical.com

EUCOBAR

EVAPORATION RETARDANT

- ◆ XENG.SPECS
- ◆ MSDS
- ◆ FRENCH
- ◆ XSPANISH
- ◆ CATALOG INDEX
- ◆ SECTION INDEX
- ◆ PRINT
- ◆ EXIT CATALOG

EUCOBAR is designed to be used as an evaporation retardant on concrete flatwork of all types. When sprayed over fresh concrete, EUCOBAR forms a thin, continuous film which prevents rapid moisture loss from the concrete surface. It is easy to use requiring only the addition of water before spray application. EUCOBAR is especially effective when concreting operations must be performed in direct sun, wind, high temperatures, or low relative humidity.

PRIMARY APPLICATIONS

- Floors
- Pavements
- Plain concrete toppings
- Dry shake floors including all SURFLEX and EUCO-PLATE formulations
- Specialty iron toppings including SUPER EUCO-TOP
- Parking decks and ramps

FEATURES/BENEFITS

- Holds in surface moisture on concrete floors, slabs, and pavements
- Helps prevent plastic shrinkage cracking
- Easy and economical to use
- Helps eliminate crusting caused by loss of surface moisture
- Useful as a finishing aid during troweling operations
- Water based for total compatibility with fresh concrete
- Excellent for both interior and exterior flatwork
- Will not effect adhesion of curing compound or other floor treatments

PACKAGING


EUCOBAR is packaged in 55 gal (208 liter) drums, 5 gal (18.9 liter) pails and 6/1 gal (3.8 liter) units per case.

TECHNICAL INFORMATION

Plastic shrinkage cracking is a strong possibility when the rate of evaporation exceeds 0.2 lb/ft²/hr (1.0 kg/m²/hr). Evaporation rate is a function of relative humidity, concrete temperature, air temperature and wind velocity. The chart below, which is fig. 2.1.5 of ACI 305, Hot Weather Concreting, is useful in determining the evaporation rate under a given set of jobsite conditions. Use EUCOBAR when the above limit is exceeded.

EUCOBAR is a water based polymer concentrate that is readily dilutable in water.

Shelf life is 2 years in original, unopened package.



Appearance

EUCOBAR is a free flowing pink liquid designed to be mixed with water. The use of EUCOBAR will not affect the color of concrete.

This product meets V.O.C. contents in accordance to EPA 40 CFR Part 59 Table I Subpart D for Floor Coatings with a maximum V.O.C. content of 400 g/l.

V.O.C.: 39 g/l

Coverage

Dilution Rate: 9:1 (water:EUCOBAR)

EUCOBAR (after dilution) will cover approximately 200-400 ft²/gal (5-10 m²/liter). Coverage will vary depending on concrete texture and wind conditions. For estimating purposes, 1 gal (3.8 liter) of EUCOBAR concentrate will treat 2000-4000 ft² (186-372 m²) of concrete surface area, but is highly dependent upon ambient conditions.

DIRECTIONS FOR USE

Surface Preparation-EUCOBAR is applied directly to the surface of fresh concrete. No surface preparation is necessary.

Mixing-Determine capacity of sprayer and divide by 10. Add this amount of EUCOBAR to the sprayer canister followed by 9 times that amount of water. For example, if 1 quart (0.95 liter) of EUCOBAR is added, dilute with 9 quarts (8.5 liter) of water. Mix or shake until thoroughly blended.

EUCOBAR is supplied as a concentrate and must be diluted with water at a 9:1 (water:EUCOBAR) ratio.

Placement-Apply using a tank type, hand pump sprayer capable of spraying in a fine mist. Use a slotted tip for the best spray. Spray EUCOBAR over the fresh concrete surface as soon as possible after bullfloating. A pink, translucent sheen will appear as the surface is treated. On extreme drying conditions, additional applications may be given as needed. When used on floors with dry shake hardener applications, EUCOBAR may be used on the fresh concrete as well as between each shake application.

Curing & Sealing-Proper curing procedures are important to ensure the durability and quality of concrete. To prevent surface cracking, cure flatwork with a high solids curing compound, such as SUPER AQUA-CURE VOX or SUPER REZ-SEAL.

CLEAN-UP

Clean spray equipment with soap and water.

PRECAUTIONS/LIMITATIONS

- Use with proper dilution rate.
- Do not use as a curing compound.
- Apply only as a fine spray.
- Do not allow to freeze.

Form Eucobar-9.99

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for six (6) months from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.