



THE EUCLID CHEMICAL COMPANY

19218 REDWOOD ROAD • Cleveland, OH 44110
(216) 531-9222 • (800) 321-7628 • FAX (216) 531-9596
www.euclidchemical.com

KUREZ VOX WHITE PIGMENTED

V.O.C. COMPLIANT, SOLVENT FREE
CURING COMPOUND

- ◆ ENG. SPECS ◆ CATALOG INDEX
- ◆ MSDS ◆ SECTION INDEX
- ✕ FRENCH ◆ PRINT
- ◆ SPANISH ◆ EXIT CATALOG

KUREZ VOX WHITE PIGMENTED is a water based liquid membrane forming curing compound for new concrete requiring a reflective curing membrane. The membrane allows the concrete to retain sufficient water in order to achieve the designed strength while providing reflectivity to minimize heat build-up in direct sun. It is 100% free of all volatile organic compounds.

PRIMARY APPLICATIONS

- Exterior paving
- Walls, columns and jersey barriers
- Residential concrete
- Sidewalks, curbs and gutters
- Bridge decks and parapet walls
- Commercial concrete

FEATURES/BENEFITS

- Forms an efficient moisture barrier for optimum curing of concrete
- Helps harden concrete through the promotion of proper cement hydration
- Suitable replacement for solvent based cures where fumes are objectionable
- Designed primarily for exterior applications where reflectivity is needed
- Absolutely free of volatile organic compounds

SPECIFICATIONS/COMPLIANCES

- This product meets all air quality standards for California, New Jersey and locales with similar clean air restrictions
- Meets ASTM C-309, Type 2, Class A & B
- Meets AASHTO M-148, Type 2, Class A & B
- Acceptable for U.S.D.A. approval
- This product meets V.O.C. contents in accordance to EPA 40 CFR Part 59 Table 1 Subpart D for Concrete Curing Compounds with a maximum V.O.C. content of 350 g/l

TECHNICAL INFORMATION

Typical Engineering Data

The following results were developed under laboratory conditions.

- Drying Time* at 73°F, 50% RH:** 1 hour
- Foot Traffic:** 2-4 hours
- Wheel Traffic:** 6-10 hours
- VOC Content:** 0 g/l
- Shelf life:** 1 year in original, unopened container.

*Low concrete or air temperatures and/or high relative humidity will extend drying time.

Appearance

KUREZ VOX WHITE PIGMENTED is a white, opaque liquid. After application and drying, the film is mottled white in appearance.

<u>COVERAGE*</u>	<u>ft²/gal (m²/liter)</u>
Smooth Concrete:	300 (7.4)
Textured Concrete:	200 (4.9)

*Coverage rates assume hard troweled floors. Coverage will vary from the above rates depending on surface porosity and texture. **AVOID EXCESSIVE BUILD-UP. THICKER APPLICATIONS MAY LEAD TO DISCOLORATION AND IMPROPER SEALER PERFORMANCE.**

PACKAGING

KUREZ VOX WHITE PIGMENTED is packaged in 55 gal (208 liter) drums and 5 gal (18.9 liter) pails.

DIRECTIONS FOR USE

Surface Preparation-This product is designed for use on fresh concrete only. The concrete surface should first be finished to the desired texture.

Mixing-Agitate before using. Material may separate during long term storage. Mild agitation is recommended before usage.

Application-Apply at a uniform coverage by spray or roller application. Product may be sprayed with a hand held "pump-up" sprayer or with an airless industrial sprayer. If roller applied, use a short-napped sleeve.

Curing-For the best cure of freshly placed concrete, apply KUREZ VOX WHITE PIGMENTED as soon as possible after finishing operations and/or immediately after the disappearance of the "sheen" of surface moisture.

REMOVAL

May be removed with pine based cleaner in water with aggressive scrubbing, or by careful use of high pressure water spray.

CLEAN-UP

Clean tools and equipment with warm, soapy water before the KUREZ VOX WHITE PIGMENTED dries.

PRECAUTIONS/LIMITATIONS

- Product is unusable if allowed to freeze. Store between 50-120°F (10-50°C).
- For best application results, product temperature should be between 50-100°F (10-38°C) with ambient and surface temperatures between 45-110°F (7-45°C).
- This product should not be used under most carpet and tile adhesives unless completely removed. Alternative options include the use of KUREZ DR VOX or EUCOSIL.
- Do not use as bond breaker for tilt-up construction.
- Do not subject to rain or water for 2 hours after application.
- Use as a curing compound only. KUREZ VOX WHITE PIGMENTED is not intended for use as a concrete sealer.
- Dried film may become milky in appearance with prolonged exposure to moisture.
- Not intended for use on architectural concrete panels unless complete removal is planned.
- For strict compliance with AIM Rule Regulations prescribed by The 1990 Clean Air Act, thinning of this product is not allowed.



Form Kurez VOX White Pigmented-11.01

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for six (6) months from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.