THE EUCLID CHEMICAL COMPANY



19218 REDWOOD ROAD • Cleveland, OH 44110 (216) 531-9222 • (800) 321-7628 • FAX (216) 531-9596 www.euclidchemical.com

EUCON WR 91

ASTM TYPE A - WATER REDUCING ADMIXTURE

◆ENG.SPECS
◆CATALOG INDEX
◆MSDS
◆SECTION INDEX
★PRINT
◆SPANISH
◆EXIT CATALOG

EUCON WR 91 is a liquid, water-reducing and plasticizing admixture for concrete. EUCON WR 91 shows improved setting and finishing characteristics when compared to other commonly used type A water reducing admixtures. EUCON WR 91 may be used at a wide range of dosage rates. EUCON WR 91 does not contain calcium chloride or other potential corrosion-enhancing ingredients.

PRIMARY APPLICATIONS

- Flatwork concrete
- · General ready mix concrete
- · Architectural concrete

FEATURES / BENEFITS

Plastic Concrete

- · Improves finishability
- · Improves workability
- Reduces water requirement
- Reduces segregation
- Improves setting times

Hardened Concrete

- · Increases strength at all ages
- Reduces permeability
- Improves finished appearance
- Reduces cracking
- · Increases durability
- Non staining
- · Compatible with air entraining agents

SPECIFICATIONS / COMPLIANCES

EUCON WR 91 meets or exceeds the requirements of:

- ASTM C-494, Type A
- AASHTO M-194
- ANSI/NSF STD 61

TECHNICAL INFORMATION

Typical Engineering Data Strength Results

Compared with reference concrete (plain mix)

Test Age	Compressive Strength	Flexural Strength
7 days	119%	108%
28 days	118%	104%

Setting Time Change - Initial +20 min.

Final +20 min.

Setting time will vary with dosage rate, mix design and ambient temperatures.

Dosage Rates

EUCON WR 91 is normally used at dosages of 2-6 fluid oz per 100 lb (125-375 ml per 100 kg) cement. Dosage recommendations depend on the characteristics of the materials being used in the mix design.

Shelf life is 1 year in original, unopened package.

DIRECTIONS FOR USE


EUCON WR 91 should be added to the sand or water. It should not come in contact with dry cement or other admixtures until they are mixed with the concrete batch. EUCON WR 91 is dispensed with automatic equipment, thus insuring uniformity of admixture use throughout the job.

PACKAGING

EUCON WR 91 is packaged in bulk, 275 gal (1041 liter) totes, 55 gal (208 liter) drums, and 5 gal (18.9 liter) pails.

PRECAUTIONS / LIMITATIONS

- Care should be taken to maintain EUCON WR 91 above freezing, however, freezing and subsequent thawing will not harm the material if thoroughly agitated. Never agitate with air or an air lance.
- · Add to mix independent of other admixtures.



WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for six (6) months from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any witten or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.